

DTCA35F-22-G-M58-AL

High Performance Industrial Lens

- DTCA series lenses are designed specially for compatibility with large sensor.
- Support newest developments in machine vision field: 24K line scan camera and 150Mp area scan camera.
- Extreme imaging aperture, extraordinary aberration correction, diffraction limited imaging resolution.
- Big aperture, good telecentricity, near zero distortion, big depth for high quality imaging.

Optical Specifications	
Magnification (x)	2.0
Object Field of View (Фmm)	22.0
Working Distance (mm)	102
Max Sensor Size (Фmm)	44
Best Aperture (F/#)	32
Telecentricity typical (max) (deg)	<0.01
Distortion typical (max) (%)	<0.045
MTF30 (lp/mm)	118-32
Depth of Field (mm)	0.16-0.64
Length of I/O (mm)	397



Field of View (mm × mm)	
CMV50000(36.43x27.62)	18.2x13.8
KAI43142 (36.18x24.12)	18.1x12.1
Mechanical Specifications	
Mount	M58
Length (mm)	282.5
Weight (kg)	1.58
Coaxial Light	NO
Iris	Yes

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

