

DTCA24K-79-M90-AL

High Performance Industrial Lens

- DTCA series lenses are designed specially for compatibility with large sensor.
- Support newest developments in machine vision field: 24K line scan camera and 150Mp area scan camera.
- Extreme imaging aperture, extraordinary aberration correction, diffraction limited imaging resolution.
- Big aperture, good telecentricity, near zero distortion, big depth for high quality imaging.

Optical Specifications	
Magnification (x)	1.11
Object Field of View (Φmm)	75
Working Distance (mm)	150±3
Max Sensor Size (Φmm)	88
Best Aperture (F/#)	7.0
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.2
MTF30 (lp/mm)	>100
Depth of Field (mm)	±0.2@F7.0
Length of I/O (mm)	641±3



Field of View (mm × mm)	
DALSA 86M (64.32x48.38)	57.9x43.6
Linescan-16K 5µm (81.9mm)	73.8
Linescan-24K 3.5µm (86.0mm)	77.5
Mechanical Specifications	
Mount	M90
Length (mm)	478.8
Weight (kg)	-
Coaxial Light	No
Iris	No

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.

