

## **DTCA121-7.3CL**

## High Performance industrial Lens

- DTCA series lenses are designed specially for compatibility with large sensor.
- Support newest developments in machine vision field: 24K line scan camera and 150Mp area scan camera.
- Extreme imaging aperture, extraordinary aberration correction, diffraction limited imaging resolution.
- Big aperture, good telecentricity, near zero distortion, big depth for high quality imaging.

Optical Specifications	
Magnification (x)	2.74
Object Field of View (Φmm)	7.3
Working Distance (mm)	64±1
Max Sensor Size (Фmm)	20(1.2")
Best Aperture (F/#)	8.5
Telecentricity typical (max) (deg)	0.005
Distortion typical (max) (%)	0.06
MTF30 (lp/mm)	>105
Depth of Field (mm)	±0.05@F7.3
Length of I/O (mm)	269



Field of View (mm ×	mm)
1.2" IMX530/540 (14.6x12.6)	5.33x4.59

Mechanical Specifications	
Mount	С
Length(mm)	188.3
Weight(kg)	/
Coaxial Light	Yes
Iris	No

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



