

DTCM110-258-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

| Optical Specifications | | |
|------------------------------------|------------|--|
| Magnification (x) | 0.064 | |
| Object Field of View (Фmm) | 258 | |
| Working Distance (mm) | 338±5 | |
| Max Sensor Size (Фmm) | 16.6(1") | |
| Best Aperture (F/#) | 6.5 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >140 | |
| Depth of Field (mm) | ±156.3@F11 | |
| Length of I/O (mm) | 804±5 | |



| Field of View (mm × mm) | | |
|---------------------------|--------|-------------|
| 1" PYTHON 5000(12.43) | (9.83) | 194.2x153.6 |
| 1" IMX255(14.19x7.5 | 1) | 221.7x117.3 |
| 1" IMX183(13.13x8.7 | 6) | 205.2x136.9 |
| Mechanical Specifications | | |
| Mount | | С |
| Length (mm) | | 448.4 |
| Weight (kg) | | 24.4 |
| Compatible Lighting | | |
| Telecentric LED Lighting | | LP270-90 |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



