

DTCM110-90-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications	
Magnification (x)	0.184
Object Field of View (Фmm)	90
Working Distance (mm)	208±3
Max Sensor Size (Фmm)	16.6(1")
Best Aperture (F/#)	6.5
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>135
Depth of Field (mm)	±18.9@F16
Length of I/O (mm)	461±3



Field of View (mm × mm)		
1" PYTHON 5000(12.43x9.83)	67.6x53.4	
1" IMX255(14.19x7.51)	77.1x40.8	
1" IMX183(13.13x8.76)	71.4x47.6	
Mechanical Specifications		
Mechanical Specifica	ations	
Mechanical Specifica Mount	ations C	
•	I	

Compatible Lighting		
Telecentric LED Lighting	DTCL-90-xW-y	
	Beam Diameter 90mm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



