

DTCM111-150-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.

Optical Specifications		
Magnification (x)	0.123	
Object Field of View (Фmm)	150	
Working Distance (mm)	300±5	
Max Sensor Size (Фmm)	18.4(1.1")	
Best Aperture (F/#)	6.2	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>145	
Depth of Field (mm)	±29@F11	
Length of I/O (mm)	671±5	

Field of View (mm × mm)				
1" IMX183 (13.13x8.76)		106.7x71.2		
1.1" IMX253 (14.19x10.38)		115.4x84.4		
Mechanical Specifications				
Mount		С		
Length (mm)		353.7		
Weight (kg)		5.8		
Compatible Lighting				
Talagantuia I ED I inhting	DTCL-150-xW-y			
Telecentric LED Lighting	Beam Diameter 150mm			

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



