

## DTCM118-100H-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications		
Magnification (x)	0.090	
Object Field of View (Фmm)	100	
Working Distance (mm)	238±4	
Max Sensor Size (Фmm)	9.0(1/1.8")	
Best Aperture (F/#)	4.6	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>200	
Depth of Field (mm)	±54.3@F11	
Length of I/O (mm)	506±4	

Field of View (mm × mm)		
1/1.8" IMX178 (7.43x4	l.9)	82.6x54.4
1/1.8" IMX252/265 (7.1x5.3)		78.9x58.9
Mechanical Specifications		
Mount		С
Length (mm)		250.1
Weight (kg)		3.1
Compatible Lighting		
Telecentric LED Lighting	DTCL-100H-xW-y	
	Beam Diameter 100mm	

## Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



