

# DTCM120-42-AL

## C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.190
Object Field of View (Φmm)	42
Working Distance (mm)	118±3
Max Sensor Size (Φmm)	8.0(1/2")
Best Aperture (F/#)	4.2
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>210
Depth of Field (mm)	±12.1@F11
Length of I/O (mm)	248±3

Field of View (mm × mm)	
1/2.5" 9P001/31 (5.7x4.28)	30.0x22.5
1/2.3" 9J003 (6.44x4.62)	33.9x24.3
Mechanical Specifications	
Mount	C
Length (mm)	112.7
Weight (kg)	0.4
Compatible Lighting	
Telecentric LED Lighting	DTCL-42-xW-y
	Beam Diameter 42mm

### Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

