

DTCM16K-216-AL

Linescan Bi Telecentric Lens

- Optimized for large field vision system with excellent imaging quality;
- Optimized for high accuracy vision system with bitelecentric design;
- Optimized for 4K and 8K line scan cameras, support 16K line scan camera and upto 47M area cameras;
- Quality guarantee by Full test report for each lens;
- Customized Mounts, F/#, DOF Etc.



Optical Specifications	
Magnification (x)	0.273
Object Field of View (Φmm)	216
Working Distance (mm)	372±5
Max Sensor Size (Φmm)	59
Best Aperture (F/#)	8.7
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>95
Depth of Field (mm)	±8.6@F16
Length of I/O (mm)	1051±5

Field of View (mm × mm)	
48.7×29.0 with KAI-47051	178.4×106.2
57.4mm with 16K×3.5/3.53um	210.3mm
57.4mm with 8K×7um/7.04um	210.3mm
Mechanical Specifications	
Mount	M72
Length (mm)	666.7
Weight (kg)	15.2
Compatible Lighting	
Telecentric LED Lighting	DTCL-216-xW-y Beam Diameter 216mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

