

DTCM230-26

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications		
Magnification (x)	0.438	
Object Field of View (Фmm)	26	
Working Distance (mm)	73±1	
Max Sensor Size (Фmm)	11.4(2/3")	
Best Aperture (F/#)	6.0	
Telecentricity typical (max) (deg)	<0.1	
Distortion typical (max) (%)	<0.1	
MTF30 (lp/mm)	>130	
Depth of Field (mm)	±2.3@F11	
Length of I/O (mm)	208±1	

Field of View (mm × mm)		
1/1.8" EV76C570 (7.2x5.4)		16.4x12.3
1/1.7" IMX226 (7.5x5.6)		17.1x12.8
2/3" IMX250/264 (8.45x7.1)		19.3x16.2
Mechanical Specifications		
Mount		С
Length (mm)		117.9
Weight (kg)		0.3
Compatible Lighting		
Telecentric LED Lighting	DTCL-26-xW-y	
	Beam Diameter 26mm	

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



