

DTCM35FH-100H-M58-AL

Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- Customized mounts available.



| Optical Specifications | | |
|------------------------------------|-----------------|--|
| Magnification (x) | 0.436 | |
| Object Field of View (Фmm) | 100 | |
| Working Distance (mm) | 238±4 | |
| Max Sensor Size (Фmm) | 43.6(35mm Full) | |
| Best Aperture (F/#) | 10.3 | |
| Telecentricity typical (max) (deg) | <0.1 | |
| Distortion typical (max) (%) | <0.1 | |
| MTF30 (lp/mm) | >91 | |
| Depth of Field (mm) | ±4.2@F20 | |
| Length of I/O (mm) | 634±4 | |

| Field of View (mm × mm) | | |
|---------------------------|----------------|----------------|
| CMV50000 (36.43x27.62) | | 83.6x63.3 |
| KAI29050/2 (36.17x24.11) | | 83.0x55.3 |
| KAI43142 (36.18x24.12) | | 83.0x55.3 |
| Mechanical Specifications | | |
| Mount | | M58 |
| Length (mm) | | 384.0 |
| Weight (kg) | | 3.8 |
| Compatible Lighting | | |
| Telecentric LED Lighting | DTCL-100H-xW-y | |
| | Beam | Diameter 100mm |

Notes:

- 1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2. Length of I/O = WD + Length + Back Focal Length.



