

# DTCM430H-216-M58-AL

## Large Format Bi-telecentric Lens

- Optimized for 4/3"~44mm M-mount or other mount cameras;
- FOV from 26mm upto 300mm;
- High resolution, low distortion and homogeneous image quality;
- Full test report for each units are provided;
- Customized mounts available.



Optical Specifications	
Magnification (x)	0.109
Object Field of View (Φmm)	216
Working Distance (mm)	372±5
Max Sensor Size (Φmm)	23.6(4/3")
Best Aperture (F/#)	4.6
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>186
Depth of Field (mm)	±53.6@F16
Length of I/O (mm)	943±5

Field of View (mm x mm)	
4/3" Keyence 21M (17.86x14.32)	163.9x131.4
4/3" PYTHON 12K (18.43x13.82)	169.1x126.8
4/3" CMV8000 (18.48x13.73)	169.5x125.9
Mechanical Specifications	
Mount	M42/M58/F
Length (mm)	559.3
Weight (kg)	14.2
Compatible Lighting	
Telecentric LED Lighting	DTCL-216-xW-y
	Beam Diameter 216mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

