

# WWK055-220-110

## Large FOV Objective Telecentric Lens

- Object side telecentric lens, support 5Mp-20Mp area scan camera.
- High definition, low distortion, good telecentricity, especially suitable for high-precision AOI and positioning applications.
- Built-in coaxial lighting, especially suitable for inspection of wafers, glass devices.
- Quickly customization apply to different camera specifications, as well as magnification, working distance, DOF requirements.



Optical Specifications	
Magnification (x)	0.55
Working Distance (mm)	220±3
Max Sensor Size (Φmm)	16(1.1")
Best Aperture (F/#)	8
Telecentricity typical (max) (deg)	≤0.1
Distortion typical (max) (%)	≤0.1
MTF30 (lp/mm)	≥110
Depth of Field (mm)	±1.1@F8
Length of I/O (mm)	452.9

Field of View (mm × mm)	
1" IMX183 (13.13x8.76)	23.9x15.9
1.1" IMX253 (14.19x10.38)	25.8x18.9
Mechanical Specifications	
Mount	C
Length (mm)	215.4
Weight (kg)	-
Coaxial Light	No
Iris	No

### Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

