

WWK40-100C-111

Large FOV Objective Telecentric Lens

- Object side telecentric lens, support 5Mp-20Mp area scan camera.
- High definition, low distortion, good telecentricity, especially suitable for high-precision AOI and positioning applications.
- Built-in coaxial lighting, especially suitable for inspection of wafers, glass devices.
- Quickly customization apply to different camera specifications, as well as magnification, working distance, DOF requirements.



Optical Specifications	
Magnification (x)	4.0
Working Distance (mm)	100±2
Max Sensor Size (Φmm)	18(1.1")
Best Aperture (F/#)	26.5
Telecentricity typical (max) (deg)	≤0.05
Distortion typical (max) (%)	≤0.01
MTF30 (lp/mm)	35
NA	0.07384
Resolution (μm)	4.5
Depth of Field (mm)	±0.07@F26.5

Field of View (mm × mm)	
1" IMX183 (13.13x8.76)	3.3x2.2
1.1" IMX253 (14.19x10.38)	3.5x2.6
Mechanical Specifications	
Mount	C
Length (mm)	187.0
Weight (kg)	-
Coaxial Light	Yes
Iris	No

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

